

541031

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 July 2004 (15.07.2004)

PCT


(10) International Publication Number
WO 2004/058654 A1

- (51) International Patent Classification⁷: **C03B 37/027**, 37/029
- (21) International Application Number: PCT/EP2002/014901
- (22) International Filing Date: 30 December 2002 (30.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **PIRELLI & C. S.P.A.** [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **COCCHINI, Franco** [IT/IT]; Via della Corte, 24, I-84013 Cava dei Tirreni (IT). **MAZZOTTI, Andrea** [IT/IT]; Via Verdi, 228/s, I-87030 Rende (IT).
- (74) Agents: **GIANNESI, Simona et al.**; Porta, Checcacci & Associati S.P.A, Viale Sabotino, 19/2, I-20135 Milano (IT).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: METHOD FOR PRODUCING AN OPTICAL FIBER HAVING LOW POLARIZATION MODE DISPERSION

(57) Abstract: Method for producing an optical fiber having low polarization mode dispersion, comprising the steps of a) providing an optical fiber preform of glass material; b) heating the glass material of an end portion of the optical fiber preform; c) drawing the heated glass material at a drawing speed V to form an optical fiber, the drawn glass material having a viscous zone (4a); d) applying to the optical fiber (4) a substantially sinusoidal spin, which is transmitted to the viscous zone (4a); characterized in that the spin function frequency ν , the viscous zone (4a) length L and the drawing speed V are such that both a torsion and at least a 50% detorsion are applied to the viscous zone (4a).



WO 2004/058654 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.